

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMPLEMENTATION PARTNER							Please tick whichever is applicable												
IL&FS Education & Technology Services Ltd. Telecommunication Cosultants India Ltd							10		V										
Telecomr	nunicati	on Cost	ultants I	ndia Ltd	d								48.00						
	U	DISE CODI	E			2	1	a	9	0	2	0	a	6	0	3			
Date								3	0	2	a	0	1	4					
School Name	G	0	V	T		S	S	D		H)	G	-		C	H	0		
	S	C	1-1	0	0	L		G	U	P	1	E	S	W	A	R			
Village	K	A	N	P	U	L	1	B	E	D	A								
Block	B	0	11	P	A	R)	G	U	D	A								
District	K	0	R	A	P	U	7												
Address	AT-	R	A	N	D	U	-	١	13	E	70	A							
	por	R	A	M	A	9	1	R	1		Pin:	7	6	4	0	4	3		
Name of Head Master/ Mistress(HM)	P	1	7	A	M	乃	A	R		-13	H	0	1						
HM Contact No.	9	5	5	6	4	0	2	0	8	9									
Name of School Coordinator	m	A	n	M	N.	S	m	I	7	A		τ	2	エ	ρ	A			
	T	9																	
School Coordinator's Contact no.	0	y	3	9	6	5	5	6	6	6									
Implementation partner's School Code	0	D	2	6	-	K	0	R	A	-	3	1	3	5					
Room Dimension (in feet)	Length:	20						Breadth		15		-				Pleas	e Tick		
Sr. no.	Ma	Item ake & Mo	del	Qty.		2	Specification & Serial No.												
1	4	Acer Make expanda					cture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher to 16GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt aker, DVD Writer, 10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots,												
		Serial no			u	X	V	8	5	S	10	1	9	D	5	2	7		
					9	4	1	3											
	Desktop(Stand by) Acer Make				expand	able to 1	.6GB, 500 er, DVD V	oz or highe GB HDD Vriter,10/ Juse With	, 19-inch 100/100	or Highe OBaseT E	r LED Mo thernet,	nitor, Bu 104 Key	illt-in at Keyboa	idio, 300	Watt	Please	e Tick		
2	5	Serial no.		1	U	X	V	8	5	S	1	0	1	8	1	5	2		
					+	8	7	6	8			5.	1			1	1. 14		

														Plea	se Tick		
3	Shared Computing Device N-computing	2	Two Shared Computing Devices per Desktop. Multibox device which allows 6 users to sha single host PC through a share computing PC-Sharing kit (which includes one full height P Card, Virtualization software, access devices with speaker output, PS/2 Mouse and PS/2 Keyboard output. SVGA Monitor output and RJ45 Connection Port. with CAT6 cables (each of 5 meters length)), Power consumption of each access device should exceed more than 1-2watts. The access device should be integrated with Host PC via CAT cable with support up to 10mtr/32ft. Each user should have independent desktop environment. User experience on shared terminal should be substantially the same as on host PC (Boot time, Login Experience, Responsiveness (Mouse, Keyboard, application state and execution), Graphics/Multimedia, Logout.										vith 5 uld not CAT 6	~	/		
	Monitor		connect	ivity with horizon	matt bl	nitor witi ack finish cal), wall Certificat	, brightne mountin	ess 250 c	d/m2, vi	wing an	gle 170	degrees/	160	Plea	se Tick		
	Serial no.					Р	ls. fill the	serial no	o.s of all	he 12 M	lonitors			n F			
	1		m	M	L	X	K	5	S	0	1	4	3	4	5		
			0	9	2	5	C	4	2	0	4						
	2		M	M	1	Y	6	5	S	0	1	4	3	4	3		
	3		1	6	7	a	2	8	2	1	0						
			M	M	L	Y	6	S	S	0	1	4	3	4	1		
		0	E	A	2	1	8	5	1	0							
	4		M	N	1	X	K	S	S	0	1	4	3	4	5		
			0	A	t	3	1)	4	2	0	4						
	5		M	M	L	×	K	S	S	0	1	4	3	4	5		
			0	A	B	8	8	4	2	0	A						
4	6	12	M	M	L	Y	6	2	5	0	1	4	3	4	4		
			0	8	4	9	A	8	5	1	0						
	7		M	M	L	4	6	S	S	0	1	4	3	A 3 A 3 A 4 A 4 A 4 A 4 A 4 A 4 A 4 A 4	1		
			0	B	2	a	6	8	5	1	D						
	8		M	M	L	X	K	S	S	0	1	A	3	4	5		
			0	8	B	D	6	4	2	0	4						
	9		M	M	L	×	K	3	S	0	1	4	3	4	5		
			6	8	6	E	F	9	2	0	4						
	10		M	M	2	×	K	S	S	0	1	9	3	4	5		
			0	B	0	B	6	4	2	0	9						
	11		M	M	L	4	6	5	S	0	1	4	3	4	4		
			0	E	7		C	8	5	1	0						
	12		M	M	L	Y	6	S	S	0	1	4	3	9	4		
¥ a.			0	B	8	3	A	8	5)	0						
5	Brand Zebronic V (Pls. tick) Wipro	1	Min 5	MP came	ra, Suppo	ort for HD	Video ca re	alling (12 eduction	80 X 720	pixels), I	Built-in n	nic with	noise	Please Tick			
6	Headphones	40 Headphone with Mic												Pleas	Please Tick		

	U DISE CODE		197		2	1	2	a	0	2	0	2	6	0	
8	Integrated Computer Projector K-YAN	1	Specification: Projection System: DLP Technology; Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA (800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4MB L3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16 GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF—in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN, Integrated analogue cable TV tuner.												e Tick
	Serial no.		1	3	10	3	0 2	20	C	-1	2	2	5	8	7
Interactive White Board Smart			Active Size: Minimum 77" diagonal Active Area: Minimum active area 156 cm W × 117cm H Resolution: Digitizing resolution is approximately 32767 x 32767 Aspect Ratio: 4:3.Board Surface: Durable Hard-coated steel surface, optimized for projection, maintenance free, compatible with dry-erase markers and easily cleaned with whiteboard cleaner or isopropyl alcohol (IPA),Operating System: Windows XP SP3, Windows Vista® SP2 or Windows 7 operating system and Linux,Writing Tools: Both finger and pen touch without any special tools, supports multi touch and use of non mechanical and battery free objects. Power Options: Power consumption is less than 0.5 W (100 mA at 5 V). Must obtain power from the computer through the USB cable for Windows® and Linux® computers. Technology: Touch technology. No interference from Electromagnetic sources/sunlight and other external influences Data Ports: 12 Mbit /s USB connection (full-speed USB 1.1 or USB 2.0). Storage: Saving of files in PC,Software: Must include a complete version of the white boarding software application on a CD or DVD. Software must also be available online for download. Users must be able to access the software without having to register for an online community. Software must be available for update via a product updating service that can automatically scan for new updates and alert users to their availability. Must support Windows® / Linux® operating systems. Should have interactive features like palm touch, image gallery, image enlarge; snap shots, recording lectures, reveal option, focus to specific part of content, zoom etc. Must supply additional software to collaborate external content and facilitate teachers to create new content and manage and deliver other content. Must supply an application for remote collaboration to work on the same content simultaneously and write directly into each other's documents. Minimum 100 to maximum 500 user can concurrently use the facility. Accessories: Stylus/ Pens, USB Cable, Software CD, user manual etc. to be a part of sta												asse Tick
ì	G 887728									-	1			3	
)	Serial no.		6	6											
10	Multi Function Printer Brand (Pis. tick) Ricoh	1	(best): U Processo 10/100B Automa	or speed: Base-T Eth tic Scann	x 600 dp Minimu ernet ne er type:	i (1200 d m 400 M etwork po Flatbed,	pi effect Hz, Conne ort, RJ-11 ADF, Scar	er, Print q ive), Disp ectivity, so Telephon on file form solution,	lay: at le tandard: ne port, l nat: JPEG	ast 2-line Hi-Speed Duplex p	d USB 2. rinting:	d	by IDC.	Pleas	se Tick
10	Multi Function Printer Brand (Pis. tick)	1	Mode: L (best): U Processo 10/100B Automa	Jp to 18 p Jp to 600 or speed: Base-T Eth tic Scann	x 600 dp Minimu ernet ne er type:	i (1200 d m 400 M etwork po Flatbed,	pi effect Hz, Conne ort, RJ-11 ADF, Scar	ive), Disp ectivity, st Telephon n file forn	lay: at le tandard: ne port, l nat: JPEG	ast 2-line Hi-Speed Duplex p	d USB 2. rinting:	d	by IDC.	Plea:	se Tick
10	Multi Function Printer Brand (Pls. tick) HP Ricoh	1	Mode: L (best): U Processos 10/100B Automa and unco ISO 9001 Pure sind Battery t UPS and tempera sine way	Jp to 18 pp to 600 pr speed: lase-T Eth tic Scann ompresse	x 600 dp Minimun ernet ne er type: id), PDF, d. Online fficiency eled. Mai With DG	i (1200 dm 400 Mi etwork pp Flatbed, I GIF, BMF	pi effect Hz, Conne Trt, RJ-11 ADF, Scan P, Scan re KVA with better on e Free, M patibilitie us, noise I	ive), Disp ectivity, so Telephorn file forn solution,	lay: at le tandard: ne port, I nat: JPEG optical: I let pour le ses powers l'Ioad, In roller Basncy range	ast 2-lini Hi-Speed Duplex p , TIF (con Jp to 12: The backup put Pow sed Double 50+/-6	d USB 2. rinting: mpresse 00 dpi, C p, Outpu er Facto ble Conv 6% hertz	t Wave Fr > 0.90, ersion O, operati	Form -	1	e Tick
	Multi Function Printer Brand (Pls. tick) HP Ricoh Serial no.		Mode: U (best): U Processo 10/100B Automa and unco	Jp to 18 pp to 600 pr speed: sase-T Eth tic Scann ompresse L Certifier e wave, Etype: Sea Cabling. ture: 0 to ture: 0 to 18 pp t	x 600 dp Minimulernet ne er type: lid), PDF, d. Online fficiency iled. Mai With DG	i (1200 dm 400 Mi etwork pp Flatbed, I GIF, BMF	pi effect Hz, Conne ort, RJ-11 ADF, Scan P, Scan re KVA with better on P Free, M patibilitie	ive), Disp ectivity, so Telephon n file forn solution, and 30 minu a rated ful icro Controls, freque	lay: at le tandard: ne port, I nat: JPEG optical: I let pour le ses powers l'Ioad, In roller Basncy range	ast 2-lini Hi-Speed Duplex p , TIF (con Jp to 12: The backup put Pow sed Double 50+/-6	d USB 2. rinting: mpresse 00 dpi, C p, Outpu er Facto ble Conv 6% hertz	t Wave Fr > 0.90, ersion O, operati	Form -	1	
11	Multi Function Printer Brand (Pis. tick) HP Ricoh Serial no. On Line UPS Delta		Mode: L (best): U Processos 10/100B Automa and unco	Up to 18 p Up to 180 Dr speed: Base-T Eth tic Scann compresse L Certifier e wave, E type: Sea Cabling. ture: 0 to re output	x 600 dp Minimun eernet ne eer type: d), PDF, d. Online fficiency eled. Mai With DG o 50 degr	UPS of 2 90 % or intenance Set comees celcie	pi effect Hz, Conne Trt, RJ-11 ADF, Scar C, Scan re KVA with better on e Free, M patibilitie us,noise I	ive), Disp ectivity, si Telephon n file form solution,	tes power load, In roller Basincy ranger the go	ast 2-line Hi-Speed Duplex p , TIF (col Jp to 12: T ar backup put Pow sed Doub e 50+/- 6 overnmen	d USB 2. rinting: mpresse 00 dpi, C	t Wave I or > 0.90, ersion O, operatis. output	Form - nline ng t: pure	1	e Tick
	Multi Function Printer HP		ISO 9001 Pure sine Battery UPS and tempera sine wav	Up to 18 p Up to 180 Dr speed: Base-T Eth tic Scann compresse L Certifier e wave, E type: Sea Cabling. ture: 0 to re output	x 600 dp Minimun eernet ne eer type: d), PDF, d. Online fficiency eled. Mai With DG o 50 degr	UPS of 2 90 % or intenance Set comees celcie	pi effect Hz, Conne Trt, RJ-11 ADF, Scar C, Scan re KVA with better on e Free, M patibilitie us,noise I	ive), Dispectivity, si Telephon n file form solution,	tes power load, In roller Basincy ranger the go	ast 2-line Hi-Speed Duplex p , TIF (col Jp to 12: T ar backup put Pow sed Doub e 50+/- 6 overnmen	d USB 2. rinting: mpresse 00 dpi, C	t Wave I or > 0.90, ersion O, operatis. output	Form - nline ng t: pure	Pleas V	e Tick
11	Multi Function Printer Brand (Pis. tick) HP Ricoh Serial no. On Line UPS Delta Serial no. Networking Networkin		ISO 9001 Pure sine Battery UPS and tempera sine wav	Jp to 18 pp to 600 pr speed: lase-T Eth tic Scann ompresses L Certifier e wave, E type : Sea Cabling. ture: 0 to re output Jumanagention pri	x 600 dp Minimun eernet ne eer type: ed), PDF, d. Online fficiency eled. Mai With DG 5 50 degr	UPS of 2 90 % or ntenance Set com ees celcio	kVA with better one a Free, M patibilities us, noise I	ive), Dispectivity, si Telephon n file form solution,	lay: at letandard: he port, I hast: JPEG optical: I letandard: let	ast 2-line Hi-Speed Duplex p , TIF (con Jp to 12: 7 Pr backup put Pow sed Doub e 50+/- 6 evernme asing cap	d USB 2. rinting: mpresse pool dpi, C go, Outputer Facto pole Conv 5% hertz nt norm:	all the n	Form - nline ng t: pure	Pleas Pleas	e Tick

	U DISE CODE	1			10	1999	Q	9		10		19	10	0	0											
14	Servo Stabilizer Protect	1	5KVA (1 Phase Servo Motor Operated Line Voltage Corrector), input Range: : 50V-270V (Single Phase), Mounting: On Wheels. Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequency range: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius.																							
	Serial no.		2	1.	0	1	1	4	0	1	1	,														
	Silent Generator Set Champ		ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation																							
15	Serial no.	1	5)	3	1	1	0	2	4	1	2	4	1	/											
16	Initial meter reading of the Silent Generator Set			0	00	00	62							Pleas	e Tie											
17	Earthing (as per IS specifications)		Copper p	late ear	thing stat	ions mak	ing earth	ning with	copper e	arth pla	te			Please Ti												
18	Lighting (ISI mark)	4	40W Tube Light with Electronic Choke (ISI mark)												e Th											
19	Ceiling / Wall mounted fans (ISI mark)	2	48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells												Please Tle											
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells												e Tie											
21		15	5 A- 240 V switches											15				- 240 V switches								
	Switches and sockets (ISI	15	2 in 1 5A and 15A Sockets																							
	Mark)	2	15 A – 240 V socket with shutter																							
	- AC		Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.																							
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated & powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided , this hole has to be covered with steel cover Good quality telescopic slider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. End caps to be provided. BIFMA Certified												Please Tid											
23	Chair Uma Plastic/Moderna	41	Armless Moulded Chairs, Cream colour, IStandard Compliant										Please Tici													
24	Electrical meter Initial reading		00007												_											
25	Painting	-	The surface OMSM are of standa	d shall b	e applied	with 2	e painted	, shall be	prepare d then w	d to the ith 2 coa	satisfact	tion of O	KCL / paint	Please	Tic											
26	Lab Cleanliness Kit	1 set	Dusting cl	oth, han					overs for	all the I	T equipr	ments ar	nd	Please T												
27	Curtains	Full lab	To mainta	in prope	r darkne	ss in the	Lab / Cla	ssroom o	luring Pro	jection				Please	Tie											
28	Wall Clock	1	ISI Mark,	Wall Clo	ck	ä								Please	Tie											
29	Notice Board	1	5feet x 3f	eet, P/F	15 thk Pi	nup boar	d with fa	bric wra	pped all a	round				Please	Tie											
30	White Board	1	4 ftx3 ft m	ninimum	18mm ti	nickness	white boa	ard						Please	771											

*** Please note that all the three signatures are mandetory on all the sheets.
****All fields are to be the any mandatorily.

Signaturova ilos son Master Mistress with Seal

Signature of OKCL Representative with Seal